

FU IPC 3400-AZ-M-AL 3.3-10.5 mm.

IP CAMERA



Key features

- 1/3" 4.0Mega progressive scan CMOS
- 4 Megapixel(2560x1440) Resolution
- Vari Focal Lens
- Support H.264 and H.265  
is twice of H.264
- Support ROI
- Support intrusion detection
- Support audio,alarm,BNC output etc
- Support Triple-Stream,Mobile APP, Support P2P
- Support reset button
- Support 2D/3D DNR, DWDR , IR CUT Filter
- Support SD Card 128 GB
- Support DC 12 Volt,PoE(Power over Ethernet)
- Day & Night
- Support Motion Detector
- IP66(Water Proof)

Product Model	FU IPC 3400-AZ-M-AL 3.3-10.5 mm.
Sensor	1/3" 4.0Mega progressive scan CMOS
Min.illumination	Colour:0.01Lux/F1.2; 0Lux/F1.2(IR ON)
Lens	3.3-10.5mm Vari-focusing lens
IR distance	30M
Electronic shutter	Auto(1/25s-1/10000s Adjustable)
Day/Night	Auto/Color / B&W (IR_CUT)
Noise Reduction	2D/3D Digital Noise Reduction
Anti-fog	Support
WDR	Digital WDR
Image Adjustment	Sharpness,Brightness,Saturation,Contrast Adjustable
Video Encoding	H.264, H.265
Encoding Type	H.265:MainProfile; H.264:High Profile/Main Profile/BaseLine Profile
Record Resolution	Main Stream: 2560*1440@20fps; Sub Stream: 704*576@20fps; Third Stream:1280*720@15fps
Video Bitrate Control	Support VBR/CBR
Video Bitrate Range	32Kbps~8Mbps
Audio	1 Audio Input ; 1 Audio Output
Alarm	1 Alarm input ; 1 Alarm output
Storage	Support TF Card, Max 128G
RS485	Support
Reset Button	Built-in reset button
CVBS output	Support
Network Interface	RJ45 10M/100M adaptive Ethernet interface IPV4 and IPV6
Motion Detection	Multiple detection zones, variable sensitivity levels
ROI	Support
Corridor Mode	Support
Privacy Masking	Four zones for privacy masking
Snapshot	JPEG capture,capture resolution is the max coding resolution
Security Features	Support password protection, watermarking features
Text Overlay	Support (Channel name and time title)
Alarm	Support network anomaly,mask alarm and etc.
Intelligent Function	Support line-crossing detection
Mobile APP.	IOS, Andriod
Network Function	TCP/IP ; UDP ; HTTP ; IGMP ; ICMP ; DHCP ; RTP/RTSP ; DNS ; DDNS ; FTP ; NTP ; PPPOE ; UPNP ; SMTP ; SNMP
Protocol	Support ONVIF and CGI protocol
Protection Grade	IP66, IK10
PoE	Support (IEEE 802.3af)
Power	DC 12V
Operation Temperature	-10 ~ +60
Operation humidity	10%--90%
Power supply	8W MAX
Dimensions	154.3mm*120.8mm
Weight	1150g