

Fu IPC BUIR 9907 Lens 3.6 mm

IP Camera



Camera	FU IPC BUIR 9907 Lens 3.6 mm.
Sensor	1/3" 4.0Mega progressive scan CMOS
Min. illumination	Colour:0.1Lux/F1.2; 0Lux/F1.2(IR ON)
Lens	3.6mm M12 lens, 6mm optional
IR distance	20M
Electronic shutter	Auto(1/25s-1/10000s Adjustable)
Day/Night	Auto/Color / B&W (IR_CUT)
Noise Reduction	2D/3D Digital Noise Reduction
Anti-fog	Support
WDR	Digital WDR
Image Adjustment	Sharpness,Brightness,Saturation,Contrast Adjustable
Video Encoding	H.264, H.265
Encoding Type	H.265:MainProfile; H.264:High Profile/Main Profile/BaseLine Profile
Record Resolution	Main Stream: 2560*1440@25fps; Sub Stream: 704*576@20fps; Third Stream:1280*720@15fps
Video Bitrate Control	Support VBR/CBR
Video Bitrate Range	32Kbps ~ 8Mbps
Reset Button	Front set reset button
Network Interface	RJ45 10M/100M adaptive Ethernet interface
Motion Detection	Multiple detection zones, variable sensitivity levels
Privacy Masking	Four zones for privacy masking
Snapshot	JPEG capture,capture resolution is the max coding resolution
Security Features	Support password protection, watermarking features
Text Overlay	Support (Channel name and time title)
Alarm	Support network anomaly,mask alarm and etc.
Intelligent Function	Support line-crossing detection
Mobile APP.	IOS, Andriod
Network Function	TCP/IP ; UDP ; HTTP ; IGMP ; ICMP ; DHCP ; RTP/RTSP ; DNS ; DDNS ; FTP ; NTP ; PPPOE ; UPNP ; SMTP
Protocol	Support ONVIF and CGI protocol
Protection Grade	IP66
PoE	Support
Power	DC 12V
Operation Temperature	-10 °C ~ +60 °C
Operation humidity	10%--90%
Power supply	5.5W MAX
Dimensions	69*69*155(mm)
Weight	530g

Features

- 1/3" 4.0Mega progressive scan CMOS
- ความละเอียดที่ 4 Mp. (2560 x 1440)
- รองรับ H.264 , H265
- รองรับ Intrusion detection , line-crossing detection
- รองรับ DWDR , Anti-Forg , 2D/3D DNR
- รองรับ POE
- รองรับ ONVIF
- รองรับ Reset Button
- ให้ความละเอียดระดับ HD (Hight Definition)
- แสงอินฟราเรดสว่างไกลถึง 20 M
- สามารถติดตั้งได้ทั้ง ภายนอกและภายใน
- ได้รับมาตรฐาน IP66
- 69X69x155mm