

Fu IP 2122

IP Dome Camera



Key features

- ความละเอียด 2 ล้านพิกเซล (1920 × 1080)
- 1/2.8" Progressive CMOS
- Full HD1080p real-time video
- 120dB Wide Dynamic Range
- 3D Digital Noise Reduction
- 3-axis adjustment ปรับระดับภาพได้ 3ทิศทาง
- 3D DNR ช่วยลดสัญญาณรบกวนในเวลากลางวัน
- ระยะอินฟราเรด 30 เมตร
- แสดงภาพคมชัดกลางวันและกลางคืน
- มี IR cut filter ช่วยให้เห็นธรรมชาติ
- IK10 ป้องกันการทุบทำลาย
- DC12V & PoE
- IP 66 (ติดตั้งได้ทั้งภายในและภายนอกอาคาร)

Fu IP 2122	
Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR 0.028Lux @ (F2.0, AGC ON) ,0 Lux with IR
Shutter Speed	1/3 s to 1/10,000 s
Lens	4mm
Lens Mount	M12
Day & Night	IR cut filter with auto switch
DNR	3D DNR
Wide Dynamic Range	120dB
P&T rotation	Pan: -90° ~ 90°, Tilt: 0° ~ 75°
Compression Standard	
Video Compression	H.264 / MJPEG/H.264+
H.264 Type	Main Profile
Video Bit Rate	32 Kbps ~ 16 Mbps
Dual streams	Support
Image	
Max. Resolution	1920 × 1080
Frame Rate	50Hz: 25fps (1920 × 1080), 25fps (1280 × 960), 25fps (1280 × 720) 60Hz: 30fps (1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
BLC	Support, zone configurable
ROI Codec	Support
Network	
Network Storage	NAS (Support NFS,SMB/CIFS), ANR
Alarm Trigger	Motion detection, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
General	One-key reset, Flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access
Standard	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
Interface	
Communication Interface	1 RJ45 10M/100M Ethernet port
On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
Alarm interface	1x alarm I/O *only for -S models
Audio interface	1x audio I/O *only for -S models
Reset	Yes

Dimensions

